

Panels raised and fielded - 12 MDF/4 HDF

Construction:	12 mm MDF	(Appr. 720 kg/m ³ - heat conductivity: 0,13 W/mK)
	Meets the standards of "Symbol H" - cf. DS/EN 316 and DS/EN 622-5 concerning MDF sheets	
	Insulation - Polystyrene	(Appr. 33 kg/m ³ - heat conductivity: 0,034 W/mK)
	4 mm HDF	(Appr.970 kg/m ³ - heat conductivity: 0,13 W/mK)

U-Value:	U-Value - W/m ² K									
Total thickness (mm)	32	34	36	40	44	48	49	51	56	60
Rebate Thickness (mm)	24	26	28	32	36	40	41	43	48	52
U-Value	1,31	1,22	1,14	1,00	0,90	0,81	0,79	0,76	0,68	0,63

Heat conductivity is calculated on the basis of the practical heat conductivity of each included material - taken from data sheets and DS418, version 6, 2002. Also relating to EN 12524.


Weight:	Weight appr. Kg./m ²									
Total thickness (mm)	32	34	36	40	44	48	49	51	56	60
Rebate Thickness (mm)	24	26	28	32	36	40	41	43	48	52
Weight	13,2	13,2	13,3	13,4	13,6	13,7	13,7	13,8	14,0	14,1

Measure: Min.: 150 x 250 mm - Max.: 1200 x 2400 mm


Tolerances: Width/Height: +/- 1 mm - Diagonal: +/- 1,5 mm - Thickness: +/- 0,8 mm

Section drawing:

Profile type F11



Profile type F12



Made: 08.12.2016	Data sheet: CRS	Draw.: CRS
Revised:	Data sheet:	Draw.:

O.H.Industri A/S
Smedevej 17
DK - 7430 Ikast
+45 9725 1200
www.ohindustri.com